

TwistPort™ Adaptor for Rocket M5

ADAPTOR FOR ROCKET™ M5

The TwistPort™ Adaptor for Rocket M5 makes the Rocket™ compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket™ M5 into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.5 Kg / 1.1 lbs – single unit incl. package 11.5 Kg / 25 lbs – carton (20 units)
Single Unit	Retail Box: 12.8 x 13.6 x 11.7 cm
20 units	Carton Box: 29 x 60.5 x 28.5 cm

PERFORMANCE

Frequency Range	5400 - 5900 MHz
Polarization	Dual Linear H + V
Cross Pol Isolation (Min)	29 dB
VSWR Max	1.8
VSWR Typical	1.4
Impedance 50 Ohm	50 Ohm
Isolation Between Ports	37 dB

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna
Ubiquiti Networks™	Rocket™ M5

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

