

# TwistPort™ Adaptor with SMA connectors

## ADAPTOR WITH TWO RP-SMA MALE CONNECTORS

The TwistPort™ Adaptor with SMA connectors is designed to provide two RP-SMA male coaxial interface (dual linear H+V) and can be connected to TwistPort™ enabled antennas.



### TECHNICAL DATA

Antenna Connection	TwistPort - Quick Locking Waveguide Port
Radio Connection	2x RP-SMA female
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.21 Kg / 0.46 lbs – single unit 0.28 Kg / 0.61 lbs – single unit incl. package 29.0 Kg / 63.9 lbs – carton (100 units)
Single Unit	Retail Box: 15.5 x 10.0 x 9.7 cm
100 Units	Carton Box: 99 x 48 x 32 cm

### PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

### COMPATIBLE WIRELESS PLATFORMS

RF elements® any TwistPort™ Antenna

### PACKAGE CONTENTS

TwistPort™ Adaptor

### PRODUCT DIMENSIONS

